



Comastri Davide
Rappresentanza industriale

Espec

Serie Platinous J

Modello	PR-1J	PR-2J	PR-3J	PR-4J	PCR-3J	PDR-3J
Temp. Range	-20 to +100 °C (+150/180°C)	-20 to +100 °C (+150/180°C)	-20 to +100 °C (+150/180°C)	-20 to +100 °C (+150/180°C)	-20 to +100 °C	-20 to +100 °C
Hum. Control	yes	yes	yes	yes	yes	yes
Hum. Range	20 to 98%rh	20 to 98%rh	20 to 98%rh	20 to 98%rh	20 to 98%rh	20 to 98%rh
Pressure Range						
Volume	120 L	225 L	408 L	800 L	312 L	408 L
Inside dimensions in mm (WxHxD)	500 x 600 x 400	500 x 750 x 400	600 x 850 x 800	1000 x 1000 x 800	600 x 650 x 800	600 x 850 x 800
Outside dimensions in mm (excl. projection)	910 x 1440 x 873	910 x 1590 x 1073				1885 x 1690 x 1273

Serie Platinous J | 1/3

Modello	PDR-4J	PHP-2J	PHP-3J	PHP-4J	PL-1J	PL-2J
Temp. Range	-20 to +100 °C	ambient temp +10 to +100 °C	ambient temp +10 to +100 °C	ambient temp +10 to +100 °C	-40 to +180 °C (+150/180°C)	-40 to +180 °C (+150/180°C)
Hum. Control	yes	yes	yes	yes	yes	yes
Hum. Range	5 to 98%rh	40 to 98%rh	40 to 98%rh	40 to 98%rh	20 to 98%rh	20 to 98%rh
Pressure Range						
Volume	800 L	219 L	398 L	784 L	120 L	225 L
Inside dimensions in mm (WxHxD)	1000 x 1000 x 800	500 x 730 x 600	600 x 830 x 800	1000 x 980 x 800	500 x 600 x 400	500 x 750 x 600
Outside dimensions in mm (excl. projection)	2285 x 1840 x 1273	910 x 1590 x 1073	1010 x 1690 x 1273	1410 x 1840 x 1273	910 x 1440 x 873	910 x 1590 x 1073

Modello	PL-3J	PL-4J	PDL-3J	PDL-4J	PSL-2J	PSL-4J
Temp. Range	-40 to +100 °C (+150/180°C)	-40 to +100 °C (+150/180°C)	-40 to +100 °C (+150/180°C)	-40 to +100 °C (+150/180°C)	-70 to +100 °C (+150/180°C)	-70 to +100 °C (+150/180°C)
Hum. Control	yes	yes	yes	yes	yes	yes
Hum. Range	20 to 98%rh	20 to 98%rh	5 to 98%rh	5 to 98%rh	20 to 98%rh	20 to 98%rh
Pressure Range						
Volume	408 L	800 L	408 L	800 L	306 L	800 L
Inside dimensions in mm (WxHxD)	600 x 850 x 800	1000 x 1000 x 800	600 x 850 x 800	1000 x 1000 x 800	600 x 850 x 600	1000 x 1000 x 800
Outside dimensions in mm (excl. projection)	1010 x 1690 x 1273	1410 x 1840 x 1273	1855 x 1690 x 1273	2285 x 1840 x 1273	1010 x 1690 x 1273	1410 x 1853 x 1593

Serie Platinous J | 2/3

Modello	PU-1J	PU-2J	PU-3J	PU-4J	PG-2J	PG-4J
Temp. Range	-40 to +100 °C (+150/180°C)	-40 to +100 °C (+150/180°C)	-40 to +100 °C (+150/180°C)	-40 to +100 °C (+150/180°C)	-70 to +100 °C (+150/180°C)	-70 to +100 °C (+150/180°C)
Hum. Control	no	no	no	no	no	no
Hum. Range						
Pressure Range						
Volume	120 L	225 L	408 L	800 L	306 L	800 L
Inside dimensions in mm (WxHxD)	500 x 600 x 400	500 x 750 x 600	600 x 850 x 800	1000 x 1000 x 800	600 x 850 x 600	1000 x 1000 x 800
Outside dimensions in mm (excl. projection)	910 x 1440 x 873	910 x 1590 x 1073	1010 x 1690 x 1273	1410 x 1840 x 1273	1010 x 1690 x 1273	1410 x 1853 x 1593

Serie Platinous J | 3/3