



Comastri Davide
Rappresentanza industriale

Espec

Serie Compatta SH-SU

Modello	SH-222	SH-242	SH-262	SH-642	SH-662	SH-242-5
Temp. Range	-20 to +180 °C	-20 to +180 °C	-60 to +180 °C	-40 to +180 °C	-60 to +180 °C	-40 to +180 °C
Hum. Control	yes	yes	yes	YES	yes	yes
Hum. Range	30 to 95%	30 to 95%	30 to 95%	30 to 95%	30 to 95%	
Pressure Range						
Volume	22.5 L	22.5 L	22.5 L	64 L	64 L	22.5 L
Inside dimensions in mm (WxHxD)	300 x 300 x 250	300 x 300 x 250	300 x 300 x 250	400 x 400 x 400	400 x 400 x 400	300 x 300 x 250
Outside dimensions in mm (excl. projection)	440 x 690 x 696	440 x 690 x 696	440 x 690 x 696	540 x 730 x 921	540 x 730 x 921	440 x 690 x 696

Serie compatta SH-SU | 1/2

Modello	U-222	U-242	U-262	U-642	U-662	U-242-5
Temp. Range	-20 to +180 °C	-40 to +180 °C	-60 to +180 °C	-40 to +180 °C	-60 to +180 °C	-40 to +180 °C
Hum. Control	no	no	no	no	no	no
Hum. Range						
Pressure Range						
Volume	22.5 L	22.5 L	22.5 L	64 L	64 L	22.5 L
Inside dimensions in mm (WxHxD)	300 x 300 x 250	300 x 300 x 250	300 x 300 x 250	400 x 400 x 400	400 x 400 x 400	300 x 300 x 250
Outside dimensions in mm (excl. projection)	440 x 620 x 696	440 x 620 x 696	440 x 620 x 696	540 x 655 x 921	540 x 655 x 921	440 x 620 x 696

Serie compatta SH-SU I 2/2