



Comastri Davide
Rappresentanza industriale

Espec

Serie LH LHL LHU LU

Modello	LH-14	LHL-114	LHU-114	LHU-124	LU-114	LU-124
Temp. Range	+10 to +85°C	+5 to +85°C	-20 to +85°	-20 to +85°C	-20 to +85°C	-20 to +85°C
Hum. Control	yes	yes	yes	YES	no	no
Hum. Range	45 to 95%rh	45 to 95%rh	45 to 95%rh	45 to 95%rh		
Pressure Range						
Volume	105 L	105 L	105 L	105 L	105 L	206 L
Inside dimensions in mm (WxHxD)	500 x 600 x 390	500 x 600 x 390	500 x 600 x 390	500 x 750 x 590	500 x 600 x 390	500 x 750 x 590
Outside dimensions in mm (excl. projection)	680 x 1090 x 826	680 x 1090 x 826	680 x 1090 x 826	680 x 1090 x 1026	680 x 1090 x 826	680 x 1090 x 1026

Serie LH LHL LHU LU | 1/2

Modello	U-222	U-242	U-262	U-642	U-662	U-242-5
Temp. Range	-20 to +180 °C	-40 to +180 °C	-60 to +180 °C	-40 to +180 °C	-60 to +180 °C	-40 to +180 °C
Hum. Control	no	no	no	no	no	no
Hum. Range						
Pressure Range						
Volume	22.5 L	22.5 L	22.5 L	64 L	64 L	22.5 L
Inside dimensions in mm (WxHxD)	300 x 300 x 250	300 x 300 x 250	300 x 300 x 250	400 x 400 x 400	400 x 400 x 400	300 x 300 x 250
Outside dimensions in mm (excl. projection)	440 x 620 x 696	440 x 620 x 696	440 x 620 x 696	540 x 655 x 921	540 x 655 x 921	440 x 620 x 696

Serie LH LHL LHU LU | 2/2