

Espec

Serie Compatta SH-SU

Modello	SH-222	SH-242	SH-262	SH-642	SH-662	SH-242-5
Temp. Range	-20 to+180°C	-20 to+180°C	-60 to +180°C	-40 to+180°C	-60 to +180°C	-40 to+180°C
Hum. Control	yes	yes	yes	yes	yes	yes
Hum. Range	30 to 95%	30 to 95%	30 to 95%	30 to 95%	30 to 95%	30 to 95%
Pressure range						
Volume	22.5 L	22.5 L	22.5 L	64 L	64 L	22.5 L
Inside dimensions in mm (WxHxD)	300 x 300 x 250	300 x 300 x 250	300 x 300 x 250	400x400x400	400x400x400	300 x 300 x 250
Outside dimensions in mm (excl. projection)	440 x 690 x 696	440x690x696	440x690x786	540x730x921	540x730x921	440x620x786

SERIE SH-SU



Comastri Davide
Rappresentanza industriale

Modello	SU-222	SU-242	SU-262	SU-642	SU-662	SU-242-5
Temp. Range	-20 to + 180°C	-40 to + 180°C	-60 to + 180°C	-40 to + 180°C	-60 to + 180°C	-40 to + 180°C
Hum. Control	NO	NO	NO	NO	NO	NO
Hum. Range	0	0	0	0	0	0
Pressure range	0	0	0	0	0	0
Volume	22.5 L	22.5 L	22.5 L	64 L	64 L	22.5 L
Inside dimensions in mm (WxHxD)	300x300x250	300x300x250	300x300x250	400x400x400	400x400x400	300x300x250
Outside dimensions in mm (excl. projection)	440x620x696	440x620x696	440x620x786	540x665x921	540x665x921	440x620x786

SERIE SH-SU



Comastri Davide
Rappresentanza industriale

SERIE SH-SU

comastridavide.com | +39 051 0217415 | info@comastridavide.com